

Product Data Sheet

HIPRO MX5

Super High Performance Multi Grade Automotive Engine Oil

PRODUCT FEATURES

High quality motor oil specially developed for optimal balance to protect the engines and deliver performance in modern cars.

APPLICATIONS

Specially formulated for passenger cars, sport utility vehicles and light trucks operating on both gasoline and diesel engines.

SPECIAL PROPERTIES

- ◆ Excellent oxidation stability and strong resistance to high and low temperature sludge formation.
- ◆ Strong engine cleanliness – maintain engine cleanliness with the detergent and dispersant additives.
- ◆ Stable in withstand high operating temperature.
- ◆ Maintains oil pressure and full lubrication even when hot.
- ◆ Providing a smooth engine protection including those fitted with turbo charged.
- ◆ Reduce friction between engine parts and helps improve fuel economy.

PERFORMANCE LEVELS

- ◆ API SL/CF

TYPICAL SPECIFICATION

PROPERTY	UNIT	TEST METHOD	SAE 20W-50
			SPECIFICATION
Density at 15 deg C	Kg/l	ASTM D4052	0.8930
Viscosity at 40 deg C	cSt	ASTM D 445	150 (typ)
Viscosity at 100 deg C	cSt	ASTM D445	17.5 – 19 .5
Viscosity Index		ASTM D 2270	122
CCS @ -25 deg C	cP	ASTM D 5293	Max 9,500
Flash Point COC		ASTM D 92	200 (min)
Pour Point	deg C	ASTM D 97	-18
Total Base Number	mgKOH/g	ASTM D 2896	6.16

* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

CAUTION: Continuous contact with used oil has caused skin cancer in lab animals. Avoid prolonged skin contact. Avoid eye contact. Wash skin thoroughly with soap and water after handling. Flush eyes with water for 15 minutes in case of contact. If swallowed, do not induce vomiting. Contact a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**
